



SHOTKING

MAKERS OF THE
WALKER PEENIMPAC

Model S-17-40 2E



The model S-17-40E eliminates the "batching" common in most machines by allowing the product to pass directly through the machine. This eliminates the downtime of loading and unloading. With very high horsepower blasting motors, the cycle time is minimal. This machine has two 25 horsepower motors to allow very fast cleaning as the parts pass through the machine. Since there is no batching, the duty cycle of this machine is 100%. Due to the open ends of the machine, typically two model CC dust collectors are needed to provide adequate vacuum. The inbound and outbound conveyor system is custom designed to interact with existing systems in your facility.

- Blasting Wheels: 2
- Horsepower: 25 each
- Basket Diameter: 16" max.
- Cycle Time: Continuous
- Footprint: 148in Wide x 54in Deep x 82in High
- Basket Speed: 2 RPM
- Dust Collector: (2) Model CC
- Cabinet: 3/16in thick Abrasive Resistant Alloy
- Construction: Bolt-together for easy replacement of components
- Electrical Consumption: 35.5 KWH
- Electrical: 3 phase, 230 volt or 460 volt
 - Nema 12 enclosure
 - All motors thermal overload protection
 - All motors totally enclosed fan cooled
- Safety: Blast wheels only operate if door is closed

(229)242-6824 • sales@shotking.com

302 South Railroad Ave. Valdosta, GA 31620 USA

www.shotking.com